

HEDY®

Guangzhou Hedy Lighting Co., Ltd.

Model	HN24H2G-300
Product	PoE Switch
Ports	
Network Ports:	26
PoE Port:	24, 100Mbps ; RJ45 ports; Max. 30W Output of Single PoE Port
Uplink Port:	2*1000Mbps RJ45 uplink ports
PWR (Power supply Indicator)	Light on: Powering Light off: No Power
SW (Mode Switch)	Green light off: Normal/Default mode
	Green light on: VLAN mode
	Green ligh flash: Extend mode
RJ-45 ACT indicator	Green light off: Link is disconnected
	Green light on: Link is connected
	Green light flash: Data Transmitting
Standard	
Network Protocol:	IEEE802.3/802.3u/802.3ab/802.3x
Performance	
Switching Capacity:	8.8 Gbps
Packet Forwarding Rate:	6.54Mpps
Packet Buffer:	1.5Mb
Forwarding Mode:	Store-and-forward
MAC Address Table:	2K
VLAN	Support
Power Over Ethernet	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+),3/6(-)
Transmission Distance:	0-100m/1000Mbps or Port 9-24 Max. 250m/10Mbps via Cat.5e or more under Extend mode
PoE Feature	All ports support MDI/MDIX
General	
Power Source:	Bult-in Power Supply
	Input: 110-240V AC, 50/60Hz
PoE Power Budget:	300W
Power Consumption:	<5W
ESD	Air discharge: 8KV
	Contact discharge: 6KV
Surge Protecton	Common mode/RJ45 port: 4KV
	Differential mode/RJ45 port: 2KV
	Common mode/Power board: 4KV
	Differential mode/Power board: 2KV
Working Temperature:	-10℃-50℃
Humidity:	10%-95% , non-condensing
Storage Temperature:	-40℃-70℃
Color	Black/Yellow
Weight:	1.44kg (not include input cable & packaging)
Dimension(L×W×H):	268*181*44 mm (L*W*H)

Product Picture

